



Incasso a muro  
con scatola  
Wall recessed box

## Stile next 503 asimmetrico

☐ = 4



IP 66 IK 06 1J xx3 CE



Predisposto per singolo ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. / Single cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy.

Lamp.	Specif.	Energy	Col.	Vetro/Glass
6 LED 220 lm 2W real output lm 32	CL.I LED €	A A+ A++		LL643C☐

☐ = N (natural white) - ☐ = 3 (3000K, lumen -5%)

## Stile next 506L asimmetrico

☐ = 4



IP 66 IK 06 1J xx3 CE



Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. / Double cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy.

Lamp.	Specif.	Energy	Col.	Vetro/Glass
6 LED 220 lm 2W real output lm 24	CL.I LED €	A A+ A++		LL663C☐

☐ = N (natural white) - ☐ = 3 (3000K, lumen -5%)

## Stile next 506L asimmetrico orizzontale

☐ = 4



IP 66 IK 06 1J xx3 CE



Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. / Double cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy.

Lamp.	Specif.	Energy	Col.	Vetro/Glass
12 LED 300 lm 3W real output lm 49	CL.I LED €	A A+ A++		LL665F☐

☐ = N (natural white) - ☐ = 3 (3000K, lumen -5%)

